## Plexiglass Metal Leg Barrier

# **Installation Instructions**

- Be sure to review complete installation instructions before you install
- Stored inside original packaging until screens are ready to be installed
- Before installation ensure the surface you're attaching the screen to is clean



#### Step One



Loosely attach the nut and bolt provided into the two holes on each metal leg.

#### Step Two



Line up the legs with the slot on the acrylic panel.

### Step Three



Peel off the protective masking on the acrylic and slide the panel into the metal legs with the slot sliding around the bolts.

#### **Step Four**



Make sure the metal legs are flat on a table surface and the acrylic panel is seated all the way down in the slot.

#### **Step Five**



Tighten the nut and bolt with the tools provided.

## Step Six




Please, DO NOT OVER TIGHTEN the nut and bolt.

# Plexiglass Metal Leg Barrier

# **Installation Instructions**



#### Step Seven



Lay the shield down and remove the red protective cover to expose the adhesive.

### Step Eight



Place the shield onto the counter in the desired location and press the feet down firmly.

# **Plexiglass Barriers**

# **Cleaning Instructions**



Cleaning Wash plexishields with dish soap and plenty of

lukewarm water. Use a clean soft cloth, applying only light pressure. Rinse with clean water and dry by

blotting with a damp cloth.

Dusting Dust with a soft, damp cloth or chamols. Dry or gritty

cloths may cause surface scratches.

Do Not Use Do not use any window cleaning sprays (Windex) or

household cleaners.